



# Series

**Hot-Water Pressure Washers** 

#1 in North America for High-Pressure Cleaning Equipment

#### **Electric / Belt Drive**

**Upright, oil fired burner** delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

**50-ft. length of high-pressure hose** for ease in cleaning

around a large area

Hose-reel slot accepts swivel or stationary reels for ease in hose management and storage **Simple, easy-to-use control panel** includes adjustable thermostat

**Heater coil** carries a 5-year warranty



**Pressure relief valve** protects the machine and user from thermal expansion

**Stainless-steel coil skin** provides extra durability to withstand the elements

**Protective cabinet** contains water resistant electical box

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

**Forklift slots** for easy lifting

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

**12" solid rubber tires** for easy maneuvering; eliminates risk of flats

Reliable, energy efficient **Hotsy Crossfire oil burner** is built to provide years of trouble free service.

Easily removable **cover** provides protection and easy access to components

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

On board wand and cord storage

**Beefy casters** for easy movement

35-ft. power cord with safety Ground Fault Circuit Interrupter (GFCI breaker)

#### **FEATURES**

- 4.0 5.0 GPM @ 2000 to 3000 PSI
- Hotsy Crossfire Oil Fired Burner
- 208V, 230V, 460V or 575V, 1PH or 3PH

Wide wheel base for stability, but 28" width easily fits through doors

■ Belt Drive Pump



**Hotsy-designed Triplex pumps** carry a 7-year limited warranty

Oil-Fired

■ 4.0 - 5.0 GPM @ 2000 to 3000 PSI

■ Hotsy 7-Year Pump Warranty

**■** Belt Drive

## Rugged design, easy maneuverability and massive cleaning power!

SPECIFICATIONS										BE	BELT DRIVE	
MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT	
821	4.0	2300	6.2	3450	208/1	33	Oil	342,900	HHC506R.2	50′	632	
842	4.0	2000	5	1725	208/3	20	Oil	342,900	HH406R.2	50′	622	
843	4.0	2000	5	1725	230/1	29	Oil	342,900	HH406R.2	50′	622	
844	4.0	2000	5	1725	230/3	19	Oil	342,900	HH406R.2	50′	622	
845	4.0	2000	5	1725	460/3	10	Oil	342,900	HH406R.2	50′	691	
851	4.0	3000	8.2	3450	208/1	44	Oil	342,900	HHC506R.2	50′	675	
852	4.0	3000	7.5	1725	208/3	25	Oil	342,900	HH406R.2	50′	665	
853	4.0	3000	7.5	1725	230/1	37	Oil	342,900	HH406R.2	50′	665	
854	4.0	3000	7.5	1725	230/3	25	Oil	342,900	HH406R.2	50′	665	
855	4.0	3000	7.5	1725	460/3	14	Oil	342,900	HH406R.2	50′	665	
856	4.0	3000	8.2	3450	575/3	11	Oil	342,900	HHC506R.2	50′	680	
873	5.0	3000	10	1725	230/1	42	Oil	395,452	HH406R.2	50′	670	
874	5.0	3000	10	1770	230/3	29	Oil	395,452	HH406R.2	50′	675	

Dimensions: 51" | x 28" w x 51" h



#### Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with specially

formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

#### Spend some time with a Hotsy Expert

Hotsy has more than 160 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's dealers have been supporting Hotsy systems for more than 20 years.

Rely on our network of seasoned service professionals for the safest,



most effective and most efficient solution to your specific cleaning need.

## Nothing Cleans Like a Hotsy!

Tel: (800) 525-1976 Fax: (888) 880-9631 www.Hotsy.com email: info@Hotsy.com
P/N 9.801-490.0 Effective 1/13 Specifications & product descriptions subject to change without notice. ©2013 Hotsy
A member of KÄRCHER North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within  $\pm\,10\%$  of listed specifications.

#### **OPTIONS for 800 SERIES**

- **8" Oil-Fired Draft Dampener** barometric; prevent backdrafts; keeps cold air out
- Auto Start / Stop, Thermal Shutdown or Time Delay Shutdown
- Hose Reels & Hose Reel Brackets

### Hotsy Accessories customize your application for top performance

no.



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe

Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping



Telescoping wands extend

to 24-ft. to reach high places without scaffolding

Distributed by: