

GAS ENGINE ROLL CAGE SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

2.7 - 4.0 GPM @ 2400 to 3500 PSI
12V DC Burners



Heavy-duty regulator rectifier
eliminates the need for battery

Stainless-steel coil skin provides extra durability
and resists corrosion

Oil-fired Wayne burner

Lifting eyes let power equipment do the hoisting

**8-gallon, removable, rust-proof polyethylene
fuel tank** has fuel gauge in cap

Protective Heavy-duty roll-cage chassis

Control box with adjustable temperature control,
hour meter and burner on/off switch

Upstream detergent injection

HOT WATER

OIL FIRED

BELT/DIRECT DRIVE

Hotsy-designed triplex direct-drive pump carries a
7-year warranty

12" heavy-duty flat free tires

50-ft wire-braided high pressure hose with swivel
on one end

Trigger gun control with cool-grip



Model 1075BE Compact:
4.0 GPM@ 3500 PSI;
Vanguard 400 engine; 12V
DC water heater (12V battery
required, not supplied)



MODEL	PART NO.	GPM	PSI	ENGINE	CCS	BURNER	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
871SS*	1.110-014.0	2.7	2400	Honda GX200	196	12V DC	248,500	HPP3035G	43"x27"x39"	410
965SSE CAL†	1.110-090.0	3.0	3000	Vanguard 400	408	12V DC	248,500	HPP3035G.1	47"x31"x41"	445
1065SSE CAL†	1.110-089.0	3.5	3000	Vanguard 400	408	12V DC	309,900	HS3540G.3	47"x31"x45"	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	389	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075SSE CAL†	1.110-080.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075BE Compact†	1.110-088.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HM4035R.3	47"x31"x45"	520
1075BE Compact†	1.110-099.0	4.0	3500	Honda GX390	389	12V DC	309,900	HM4035R.3	47"x31"x45"	520

*Battery not required † 12V battery required, but not supplied E = Electric-start engine B=Belt

WARNING: This product can expose you to chemicals including Lead and Diisononyl Phthalate, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

HOTSY.COM

NOTHING CLEANS LIKE A HOTSY!

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models, and subject to change without notice. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_ 10% and in some cases are tighter within +_ 5% of listed specifications.

Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2025 Kärcher North America
P/N HOT_GasEngineRollCage Effective 03/25

Distributed by: